

# Tubi in materiale plastico

## PVC hoses

### DALSPIR MET

Tubo atossico molto flessibile e robusto in pvc trasparente plastificato con spirale di rinforzo in acciaio armonico zincato antisciacchiamento. Interno ed esterno lisci, atossico secondo DM 21/3/73 e successivi aggiornamenti, direttiva CEE 90/128 e modif che.

Applicazioni: aspirazione e mandata liquidi in agricoltura, edilizia, industria, per macchine agricole e industriali di ogni genere.

Temperatura d'impiego: -15°C +65°C.

Colore: trasparente

Non-toxic galvanized steel spiral PVC hose, internal and external smooth surfaces according to DM 21/3/73 ( Italy) and EEC 98/128.

Applications: suction and delivery for industrial and agricultural machinery

Working temperature: -15°C +60°C

Colour: transparent



| CODICE<br>CODE | DIAMETRO<br>NOMINALE mm<br>NOMINAL BORE mm | LUNGHEZZA ROTOLO m<br>ROLL LENGHT m | PESO g/m<br>WEIGHT g/m | PRESSIONE ESERCIZIO bar<br>WORKING PRESSURE bar | SOTTOVUOTO m H <sub>2</sub> O<br>VACUUM m H <sub>2</sub> O |
|----------------|--|-------------------------------------|------------------------|---|--|
| TFP12612       | 12   | 60                                  | 180                    | 8,0   | 9,0  |
| TFP12614       | 14   | 60                                  | 230                    | 8,0   | 9,0  |
| TFP12616       | 16   | 60                                  | 270                    | 8,0   | 9,0  |
| TFP12618       | 18   | 60                                  | 300                    | 7,0   | 9,0  |
| TFP12620       | 20   | 60                                  | 340                    | 7,0   | 9,0  |
| TFP12622       | 22   | 60                                  | 380                    | 6,0   | 9,0  |
| TFP12625       | 25   | 60                                  | 500                    | 6,0   | 9,0  |
| TFP12630       | 30   | 60                                  | 600                    | 5,0   | 9,0  |
| TFP12632       | 32   | 60                                  | 650                    | 5,0   | 9,0  |
| TFP12635       | 35   | 60                                  | 750                    | 5,0   | 9,0  |
| TFP12638       | 38   | 30                                  | 800                    | 4,5   | 9,0  |
| TFP12640       | 40   | 30                                  | 930                    | 4,5   | 9,0  |
| TFP12645       | 45   | 30                                  | 1150                   | 4,5   | 9,0  |
| TFP12650       | 50/51                                      | 30                                  | 1450                   | 4,0   | 8,5  |
| TFP12660       | 60   | 30                                  | 1800                   | 4,0   | 8,5  |
| TFP12670       | 70   | 30                                  | 2100                   | 3,5   | 8,5  |
| TFP12675       | 75/76                                      | 30                                  | 2300                   | 3,5   | 8,5  |
| TFP12680       | 80   | 30                                  | 2500                   | 3,0   | 8,5  |
| TFP12690       | 90   | 30                                  | 2900                   | 3,0   | 8,5  |
| TFP126100      | 100/102                                    | 30                                  | 3700                   | 3,0   | 8,5  |